

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
1	Product name	901 Grade A	Volt-Amp Rating	Watt Rating @ PF	Input Voltage Range	Mounting Options	Unit Type	Half Load runtime	Full Load runtime	Height	Width (17" fits 19" rack)	Depth	"Backed Up" Electrical Outlets	Other Outlets	Rated AC Energy Absorption	Control connections	Other Features	Notes
2	Powerstar UPS - Model PS-10000		10000	8000	200 - 240	Rack	OnLine	13	4	11	17	27	5	NEMA, Mil*	na	Serial, Ethernet	Display, Expandable, Alarms, Bypass	Dual pole circuit breaker, intelligent UPS, 1 or 2 phase input delta power, 1 phase output, 2000W @32 minutes, steel case
3	Powerstar UPS - Model PS-10000i		10000	8000	200/415	Rack	OnLine	13	4	11	17	27	5	IEC, Mil*	na	Serial, Ethernet	Display, Expandable, Alarms, Bypass	6u x26.5"d 10kva 8000w output This can be connected to 1 or 3 phase Ysystem input with 1 phase output. For shipboard applications. Extend the temperature range to -25 to +60°C with our premium battery pack
4	PS10000-GXT NEW!!		10000	8000	208/220	rack	online	14	5	11	17	26	6	IEC, Mil,	na	serial, Ethernet	Display, Expandable, Alarms, Bypass	Dual pole circuit breaker, intelligent UPS, 1 or 2 phase input delta power, 2 phase output, 110 and 220 can both be delivered on outputs Add additional battery packs , steel case
5	Powerstar UPS PS6006rm3U NEW!!		6000	4200	160-280	Rack	Online	16	5.3	5.3	17	26	4	(2) NEMA L6-20R & (2) L6-30R or 5-20r and L6-30 or MIL.	480 j	Serial, Ethernet	Display, Expandable, Alarms, internal Bypass (Auto and Manual)	Dual pole circuit breaker, Dual 120/220 outputs, or single V output. Steel case intelligent UPS, 1 phase input Shipboard delta power 120Lb.Net weight 1040.00 BTU/hr Emergency Power Off EPO, mounting rails included , 1200watts @32 minutes. (Opt. Add-on up to 10ea. 3Ux26" battery trays, 200Lb Ea. 1920 VA/Hr.) NEW!!!
6	Powerstar UPS - Model PS-6005rm3u		5000	4000	155-257	Rack	Online	26	9	5.1	17	26	6	(4)5-20, (1) L14-30r, (1)L6-30r or MIL.	365j	Serial, *Ethernet	Display, Expandable, Alarms, Bypass	Features: The new PS6005 UPS is loaded with features, and packed with power performance protection. FCC class A and UL approved. Shipboard ready, Built in internal auto /manual bypass, Outputs both 120V and 208V. outlets on back for both voltages.Extend the temperature range with our premium battery pack
7	Powerstar UPS - Model PS-6005rm7u- Glups© Shallow depth		5000	4000	155-257	Rack	Line Interactive	26	9	12	17	16	4	2@6-20 2@6-30 , Mil*, IEC*	480 joules	Serial, *Ethernet	Display, Expandable, Alarms, Bypass	Global Power, Dual pole circuit breaker, intelligent UPS, 1 phase input delta power (5u) 8.75x19x22"D, 2u 240/110v transformer *, International version
8	Powerstar UPS - Model PS-6003RM-2u		3000	2700	82-144	Rack	Line Interactive	11	3	3.5	17	26	8	NEMA 5-15R and 5-20R, Mil *	480 joule	Serial, *Ethernet	Display, Alarms, Bypass, Hotswap	3kva 2700W shipboard UPS in low profile 2u x26"d chassis.This unit can be ordered to MIL810F transport and temp ratings with our Premium or N series battery. Install an Ethernet card and use Powerchute software to control this unit from afar.
9	Powerstar UPS - Model PS-6003Tower NEW!!		3000	2700	82-144	Tower	Line Interactive	15	4	17	7.7	22	10	NEMA 5-15R and 5-20R, Mil *	480 joule	USB, Serial, *Ethernet	Alphanumeric Text Display for setup and Alarms, Hotswap batteries	3kva 2700W shipboard UPS in vertical format. Hull mounting kit available. Large internal Battery supply. New Text readout of status and alarms on front panel.Increase temp ratings with our Premium or N series battery. Install an Ethernet card and use Powerchute software to reset units by flashing their power with the Switchable Outlet Group Feature.

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
1	Product name	901 Grade A	Volt-Amp Rating	Watt Rating @ PF	Input Voltage Range	Mounting Options	Unit Type	Half Load runtime	Full Load runtime	Height	Width (17" fits 19" rack)	Depth	"Backed Up" Electrical Outlets	Other Outlets	Rated AC Energy Absorption	Control connections	Other Features	Notes
10	Powerstar UPS - Model PS-6003RM-4u-The 2+2 Shallow depth		3000	2700	82-144	2 pieces can be racked separately	Line Interactive	11	3	3.5	17	18	8	NEMA 5-15R and 5-20R, * separate breakers for each outlet pair, *Mil	480 joule	Serial, *Ethernet	Display, Expandable, Alarms, Bypass, Hotswap batteries	Only 18" deep, 3.5" tall- Battery tray is separate from 3.5" Electronics tray- great if you are tight for space, shutdown software, delta power dual pole breaker, EPO, MIL or NEMA connectors , 220V model*
11	Powerstar UPS - Model PS-6003RM4u-18A-The 2+2 grade A NEW!!	yes	3000	2700	82-144	2 pieces can be racked separately	Line Interactive	11	3	3.5	17	18	8	NEMA 5-15R and 5-20R, * separate breakers for each outlet pair, *Mil	480 joule	Serial, *Ethernet	Display, Expandable, Alarms, Bypass, Hotswap	Now being built to MIL901D-A specs. Only 18" deep, 3.5" tall- Battery tray is separate from 3.5" Electronics tray, Daisychain on more trays for Runtimes. delta power dual pole breaker, EPO, MIL or NEMA connectors , 220V model available
12	Powerstar UPS -- Model PS-6003RM-3uXL Obsolete		3000	2700	82-144	Rack	Line Interactive	15	5.4	5.3	17	26	11	NEMA 5-15R and 520R, battery, *MIL	880 joule	Serial, *Ethernet	Display, Expandable, Alarms, Bypass	See PS6003rm2uXL Powerchute shutdown software, 3Ux19x26"D, delta power dual pole breaker, EPO, mil or NEMA connectors, add up to 10 additional battery trays
13	Powerstar UPS - Model PS-6003RM2uXL NEW!		3000	2700	82-144	Rack	Line Interactive	15	5.4	3.5	17	26	11	NEMA 5-15R and 520R, battery, *MIL	880 joule	Serial, *Ethernet	Display, Expandable, Alarms, Bypass	New higher efficiency now 98% ; Very similar runtimes to the old PS6003rm3uXL Powerchute shutdown software, 2Ux19x26.9"D, delta power dual pole breaker, EPO, mil or NEMA connectors, add up to 10 additional 2U battery trays
14	PS-6003RM-3u-ISO		3000	2700	82-144	Rack	Line Interactive	15	5.4	5.3	17	26	11	NEMA 5-15R and 520R, battery, *MIL	880 joule	Serial, *Ethernet	Display, Expandable, Alarms, Bypass	Powerchute shutdown software, 3Ux19x26"D, delta power dual pole breaker, EPO, mil or NEMA connectors, Internal Isolation transformer. Battery is similar to PS6003rm2u performance. Stainless steel or Galvaneel chassis
15	Powerstar UPS - Model PS-6003RM-5u Shallow Depth		3000	2700	82-144	Rack	Line Interactive	14	4.5	8.8	17	19	8	2@L6-20, 2@L6-30, *MIL	880 joule	Serial, *Ethernet	Display, Expandable, Alarms, Bypass	Powerchute shutdown software, 8.75x17x18.5"D, delta power dual pole breaker, EPO, mil or NEMA connectors Steel case. Shallow depth problem solver
16	Powerstar UPS - Model PS3300rm2u IMPROVED!!		3000	2700	120	Rack	OnLine	9.5	4	3.5	17	24	4	L5-15, L5-30, *MIL	IEEE 587 A,B	Serial, *Ethernet	Display, Expandable, Alarms, Bypass	Delta, Intelligent, modular, rugged welded packaging 3.5"X19X25"d, Elgar PDU connector optional Improved motherboard now supports up to 2700W loads
17	Powerstar UPS - Model PS3300rm3u-ISO ELGAR		3000	2700	60-140	Rack	OnLine	9.5	4	5.3	17	24	4	L5-15, L5-30, *MIL	IEEE 587 A,B	Serial, *Ethernet	Display, Expandable, Alarms, Bypass	Delta, Isolation transformer, Intelligent, modular, Stainless steel rugged welded packaging, 5.25"X19X25"d Wired to be controlled by Elgar 2000 PDU

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
1	Product name	901 Grade A	Volt-Amp Rating	Watt Rating @ PF	Input Voltage Range	Mounting Options	Unit Type	Half Load runtime	Full Load runtime	Height	Width (17" fits 19" rack)	Depth	"Backed Up" Electrical Outlets	Other Outlets	Rated AC Energy Absorption	Control connections	Other Features	Notes
18	Powerstar UPS - Model PS3300rm3u-LCS Grade A	yes	3000	2700	60-140	Rack	OnLine	9.5	4	5.3	17	24	4	MS3102r1 6-10s, L5-15	IEEE 587 A,B	Serial, *Ethernet	Display, Expandable, Alarms, Bypass	Delta, Mil 901D, 167, 1399* accepted, Isolation transformer, Beautiful Stainless steel fully welded chassis , 5.25"X19X25"d, EMI/RFI gaskets & window included, ext. Batt connector for extended runtime, EPO, Add EMI internal filter if you need it. 4 high performance fans inside.
19	PS-6002rm3uXL Obsolete see below		2200	1980	82-147	Rack	Line Interactive	29	8.2	5.3	17	26	11	NEMA 5-15R and 5-20R	880	Serial, *Ethernet	Display, Alarms, Bypass, Hotswap	OBsolete This rugged 2.2 kva 1980 watt rackmount 3U x 26" deep UPS .Battery connector for external battery packs. Extend the temperature range with our premium battery pack
20	PS-6002rm2uXL NEW!		2200	1980	82-147	Rack	Line Interactive	29	8.2	5.3	17	26	11	NEMA 5-15R and 5-20R	880	Serial, *Ethernet	Display, Alarms, Bypass, Hotswap	Similar specs to the discontinued PS6002rm3uXL (above) in a 3.5" height. This rugged 2.2 kva 1980 watt rackmount 2U x 26.9" deep UPS is the new price/performance leader with 98% efficiency for shipboard or mission critical applications. Can also be supplied as PS6002rm2uxli 230VAC model. Modular "all-in-one" construction can have Web-intelligent Network card added. 830W for 30 minutes. Battery connector for external 2Ux 27" battery packs. Extend the temperature range with our Premium battery pack
21	Powerstar UPS - Model PS-2200		2200	1980	82-144	tower	Line Interactive	24	6.5	17	8	22	6	NEMA 5-15, L5-15, *MIL	459 joules	Serial, *Ethernet	Display, Alarms, Bypass	PS2200 floor standing or hull mount. with steel case. Large battery pack gives long runtimes. Optional hull mounting kit with steel straps and mounting plate. Also available with 208 or 230VAC in/out. NEMA 5-15r but other output connectors available Extend the temperature range with our premium battery pack . Same as our PS2201SS grade A without the stainless top cover and additional ruggedization.
22	Powerstar UPS - Model PS-2201 Grade A	yes	2200	1980	82-144	tower	Line Interactive	24	6.5	17	8	22	6	MS3102r1 6-10s or NEMA	459	Serial, *Ethernet	Display, Alarms, Bypass	Grade A -Mil 901D, 167, vibration and shock approved, non magnetic, hull mount avail. Low smoke cable, EMI filter, Hi-G Breaker, Tower shaped UPS, Optional connectors
23	Powerstar UPS - Model PS-6002rm2u		2200	1980	82-147	Rack	Line Interactive	29	8.2	3.5	17	26	11	NEMA 5-15R and 5-20R	880	Serial, *Ethernet	Display, Alarms, Bypass, Hotswap	Powerchute shutdown software, 2Ux19x26"D, delta power dual pole breaker, EPO, mil or NEMA connectors, steel case
24	Powerstar UPS - Model PS3200rm2u or PS3200rm2ui NEW!		2000	1800	85-140, 200-260	Rack	OnLine	16	5	3.5	17	24	6	L5-15, *Mil	IEEE 587 A,B	Serial, *Ethernet	Display, Expandable, Alarms, Bypass, HotSwap	New increased PF! Rugged shipboard, global, or mission critical UPS 3.5x17x19.7"d, steel case, All our true online double conversion units can change the output frequency if you need it. International voltage range "I" model avail.
25	Powerstar UPS - Model PS3200rm-3u-ISO		2000	1800	85-140 or 200-260v	Rack	OnLine	16	5	5.3	17	24	6	L5-15, *Mil	IEEE 587 A,B	Serial, *Ethernet	Display, Alarms, Bypass, HotSwap	Isolation transformer, Rugged shipboard, global, or mission critical UPS, 5.25x19x23.5"d Galvaneal (zinc/iron alloy) Steel enclosure, Delta power

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
1	Product name	901 Grade A	Volt-Amp Rating	Watt Rating @ PF	Input Voltage Range	Mounting Options	Unit Type	Half Load runtime	Full Load runtime	Height	Width (17" fits 19" rack)	Depth	"Backed Up" Electrical Outlets	Other Outlets	Rated AC Energy Absorption	Control connections	Other Features	Notes
26	Powerstar UPS - Model PS3150		1550	1350	85-140 or 200-260v	Rack	OnLine	13	4	3.5	17	18	4	L5-15, *Mil	IEEE 587 A,B	Serial, *Ethernet	Expandable, Alarms, Bypass	Intelligent, modular, rugged steel packaging, 3.5x16.9x19.7"d
27	Powerstar UPS - Model PS3150rm-3u-ISO		1550	1350	60-140	Rack	OnLine	13	4	5.3	17	21	4	L5-15, *Mil	IEEE 587 A,B	Serial, *Ethernet	Display, Expandable, Alarms, Bypass, HotSwap	Galvanic Isolation Transformer, Galvaneal steel rugged packaging 5.25x17x21 , countersunk top and bottom retaining screws.
28	Powerstar UPS - Model PS1504 SMT		1500	980	82-144	tower	Line Interactive	23	6.5	8.5	6.75	17	8	NEMA, *Mil	459	Serial, *Ethernet	Display, Alarms, Bypass	This low cost UPS is the leader with power range of 1500va, 1050W output. This is a tower shaped unit. 8.5"h x6.75"w x16.75" d. A Deck Mounting kit is available. NEW!Text Readout on Front panel to change parameters or read back Status or Alarms.
29	Powerstar UPS - Model PS1503 Grade A	yes	1500	980	82-144	tower	Line Interactive	23	6.5	8.5	6.75	17	6	Mil, L5-15	459	Serial, *Ethernet	Display, Alarms, Bypass	Best seller! Rugged stainless steel, non-magnetic, delta power, shipboard proven 8.5x6.75x16.75"D, Mil 901D, 167, Barge tested, AVR
30	Powerstar UPS - Model PS1503 AVD GLUPS©		1500	980	82-144 / 165-280	tower	Line Interactive	23	6.5	8.5	6.75	17	6	Mil, *NEMA	459	Serial, *Ethernet	Display, Alarms, Bypass	Global power, AVD-Auto Voltage Input Detection for CONUS and OCONUS, Rugged stainless steel, delta power, shipboard proven 8.5x6.75x16.75"D, AVR, GLUPS
31	Powerstar UPS - Model PS6000isoA grade A	yes	1500	980	82-144	Rack	Line Interactive	16	5	5.3	17	22	2	MS3102r1 6-10s		Serial, *Ethernet	Display, Alarms, Bypass, HotSwap	Best Seller! Tested for Mil901d, 461, Grade A, Isolation transformer, Rugged shipboard, global, or mission critical UPS, Mil input & output 5.25x17x21.5"d Stainless Steel enclosure, Delta, Let us know what connectors you want.
32	Powerstar UPS - Model PS6000rm3u-ISO		1500	980	82-144	Rack	Line Interactive	16	5	5.3	17	15	6	5-15, L5-15	459	Serial, *Ethernet	Display, Alarms, Bypass, HotSwap	Isolation Transformer, Rugged shipboard, global, or mission critical UPS, 5.25x19x15"d Stainless Steel enclosure, Delta, USB
33	Powerstar UPS - Model PS6000rm3u-220		1500	980	82-144	Rack	Line Interactive	16	5	5.3	17	18	4	2@ IEC C14/13, 2 @L6-20r	459	Serial, *Ethernet	Display, Alarms, Bypass, HotSwap	Output Transformer, 220V output 110V input, Rugged shipboard, global, or mission critical UPS, 5.25x19x18"d Stainless Steel enclosure, Delta, USB
34	Powerstar UPS - Model PS6000-1rm3u		1500	980	82-144	Rack	Line Interactive	16	5	5.3	17	15	6	5-15, L5-15	459	Serial, *Ethernet	Display, Alarms, Bypass, HotSwap	Rugged shipboard, global, or mission critical UPS, 5.25x19x15"d Stainless Steel enclosure, Delta, USB no isolation transformer
35	Powerstar UPS - Model PS-502-1500LCD		1500	865	100-128	tower	Line Interactive	10	5.3	8.7	5.1	14	6	5-15	340	USB	LCD Display, Alarms	Low Cost unit, Hi-temp battery with 8-10 year life, Auto Voltage regulator. 8.7x5.1x13.8". Wired for shipboard power, dual pole breaker Stepped Full Sinewave output
36	Powerstar UPS - Model PS-1501rm		1440	980	82-144	Rack	Line Interactive	23	6.5	5.3	17	18	2	Mil, *NEMA	459 joules	Serial, *Ethernet	Display, HotSwap, Alarms, Bypass	Stainless steel chassis Dual pole circuit breaker, delta power, modular design non-magnetic, SNMP ready, Isolation Transformer opt., Hi temp batteries avail.
37	Powerstar UPS - Model PS6000rm2u		1440	980	82-144	Rack	Line Interactive	26	7.4	3.5	17	18	6	5-15, L5-15	459	Serial, *Ethernet	Display, Alarms, Bypass, HotSwap	Rugged shipboard UPS, 3.5x19x18"d Steel enclosure, Delta,USB

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
1	Product name	901 Grade A	Volt-Amp Rating	Watt Rating @ PF	Input Voltage Range	Mounting Options	Unit Type	Half Load runtime	Full Load runtime	Height	Width (17" fits 19" rack)	Depth	"Backed Up" Electrical Outlets	Other Outlets	Rated AC Energy Absorption	Control connections	Other Features	Notes
38	Powerstar UPS - Model PS503-1000 Tower		1000	900	60-140	Rack or tower	OnLine	12	4	8.9	6.9	15	4	5-15, L5-15, *Mil	IEEE 587 A,B	USB, *Ethernet	Expandable, Alarms, Bypass, HotSwap	Delta, Auto and Manual bypass, Full sine, all the features of a Much more expensive UPS in a lower power level.
39	Powerstar UPS - Model PS-502-750G		750	450	105-128	STRIP	Line Interactive	6	2.3	3.5	7.1	14	5	5-15	365	USB	Alarms	Low cost, 3.48x7.09x13.49" 3 outlets have hibernate state 'Master control' Dual breaker Delta power wired, for PC, Brick shape thick shock resistant plastic case. This will connect directly to USB and Windows will recognize it with no additional software for controlled shutdown during Power Failure. Great for a PC and Display. Quasi Sine
40	Powerstar UPS - Model PS503 Convertible		700	630	60-140	Rack or tower	OnLine	17	6	3.5	17	17	4	5-15, L5-15, *Mil	IEEE 587 A,B	USB, *Ethernet	Expandable, Alarms, Bypass, HotSwap	Delta, Auto and Manual bypass, 3.5x19x17"d Full sine output, USB, All the features of the larger High powered UPS with the Low Cost Solution
41	Powerstar UPS - Model PS3070rm2u		700	630	60-140	Rack	OnLine	17	6	3.5	17	17	4	5-15, L5-15, *Mil	IEEE 587 A,B	USB, *Ethernet	Expandable, Alarms, Bypass, HotSwap	Delta, Auto and Manual bypass, 3.5x19x17"d Full sine
42	Powerstar UPS - Model PS3070rm3u-ISO		700	630	60-140, 240	Rack	OnLine	17	6	5.3	17	17	4	5-15, L5-15, *Mil	IEEE 587 A,B	USB, *Ethernet	Expandable, Alarms, Bypass, HotSwap	Galvanic isolation transformer, auto and manual bypass, 5.25x19x 17"d, 240 or 120V GLUPS©
43	Powerstar UPS - Model PS-700-VI		700	630	95 to 255	Rack	OnLine	17	6	3.5	17	15	1	NEMA, *mil	IEEE 587 A,B	Serial	Expandable, Alarms, Bypass, HotSwap	Delta, All metal shell for rugged operation, shielded connectors Global UPS (GLUPS) Rack Mount
44	Powerstar UPS - Model PS-502-650		650	390	105-128	STRIP	Line Interactive	8	4.2	3.5	12.6	7	4	5-15	365	USB	Alarms	Low Cost, Delta wired Dual pole breaker, USB cable included, shutdown PC Software, Brick shaped plastic case. Windows knows this UPS if connected with USB.
45					Most units can also be built in Euro voltages 230V.	See notes col. R								Standard outlets listed. Most units can be optioned with Mil Spec connectors.		USB is provided on most all units. Some contain DB9 Serial as well. Ethernet is optional on most units. SNMP, HTTP,	Features; Full Sinewave output, Internal Diagnostics, Remote shutdown capability, Software to monitor and adjust UPS included., Audible or visual or remote alarm outputs. Display means LED or LCD indicators showing unit status	, All Rack units come with Steel mounting rail kits for installing into a 19" 4 post equipment rack. The Floor mount towers can be purchased with a steel weldable foundation plate with padded metal straps to securely hold the unit in place.